## ENVELOPE LEAKAGE TEST REPORT (Blower Door Test) Residential Prescriptive, Performance or ERI Method Compliance 2023 Florida Building Code, Energy Conservation, 8th Edition

| Jurisdiction:   |  |  | Permit #:  |
|---|--|--|--|
| Job Information   |  |  |  |
| Builder:  | Communit   | y:   | Lot:   |
| Address:  |  |  |  |
| City:   | State:   | FL   | Zip:   |
| Air Leakage Test Results Passing results must meet either the Performance, Prescriptive, or ERI Method  |  |  |  |
| Prescriptive Method—Th<br>changes per hour at a pressure  |  |  | sted and verified as having an air leakage rate of not exceeding 7 air ate Zones 1 and 2.  |
| the selected ACH(50) value, as section ACH50.   | shown on Form R405—2023  | (Perforn   | all be tested and verified as having an air leakage rate of not exceeding mance) or R406—2023 (ERI), section labeled as infiltration, sub-<br>Performance) or R406—2023 (ERI):   |
| 0   |  | Me<br>O  | Method for calculating building volume:  D. Retrieved from architectural plans   |
| CFM(50) × 60 ÷ Buildir  | ng Volume ACH(50)  | 0  | Code software calculated   |
| 10) 60  |  | 0  | Field measured and calculated  |
| R402.4.1.2 Testing. The buildinger hour in Climate Zones 1 and than three air changes per hour and Section M1507.3 of the Fiker reported at a pressure of 0.2 in Florida Statutes, or individuals results of the test shall be signified after creation of all penetrations. Exception: Testing is not rule in which the new construction During testing:  1. Exterior windows and do infiltration control measures.  2. Dampers including exhall infiltration control measures.  3. Interior doors, if installed Exterior doors for continues. Heating and cooling systems. Supply and return registers. If an attic is both air seal and the attic shall be open. | ing or dwelling unit shall be tested 2, and three air changes per I in shall be provided with whole-horida Building Code, Residentia ich w.g. (50 pascals). Testing si licensed as set forth in Section and by the party conducting the its of the building thermal envelouequired for additions, alteration on is less than 85 percent of the party conducting the state of the party conducting the section on its less than 85 percent of the party conducting the state of the party conducting the part | ed and voor in Couse me Andrews 100 to 100 t | e closed, but not sealed, beyond the intended weatherstripping or other discovery sentilators shall be closed and sealed.  It, shall be turned off.  It is hall be fully open.  It is access doors and hatches between the conditioned space volume for purpose. |
| Testing Company   |  |  |  |
| Edition) requirements accord  | ling to the compliance metho   | d selec  |  |
| Signature of Tester:  |  | Date   | e of Test:   |
| Printed Name of Tester:   |  |  |  |
| License/Certification #:  |  | leeu   | uing Authority:  |